Lenovo Broadcom 5719 Interno Ethernet 1000 Mbit/s



Marca : Lenovo

Código del producto: 4XC7A08235

Nombre del producto : Broadcom 5719

Lenovo Broadcom 5719. Interno. Tecnología de conectividad: Alámbrico, Interfaz de host: PCI Express, Interfaz: Ethernet. Rango máximo de transferencia de datos: 1000 Mbit/s. Color del producto: Verde, Acero inoxidable

Puertos e Interfaces	
Tecnología de conectividad *	Alámbrico
Interfaz de host *	PCI Express
Interfaz *	Ethernet
Ethernet LAN (RJ-45) cantidad de puertos	4
Verisión PCI	2.0

Conexión	
Rango máximo de transferencia de datos *	1000 Mbit/s
Estándares de red *	IEEE 1588, IEEE 802.1Q, IEEE 802.1as, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z
Ethernet	✔
Tipo de interfaz ethernet	Gigabit Ethernet
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s
Conexión de redes	✔
Controlador LAN	Broadcom BCM5719

Diseño	
Componente para *	Servidor
Color del producto	Verde, Acero inoxidable
Interno *	✔
Certificación	EN55022, EN55024, EN60950 / CE, EN 61000-3-2, EN 61000-3-3, ICES-003, Issue-004, IEC 950 CB Scheme, FCC 47 CFR Part 15 Class A, UL 1950, CSA C22.2 950-95, VCCI, AS/NZSCISPR 22 / C-tick, RRL for KC, BSMI, UL 94-/V
Productos compatibles	R635 (7Y98 / 7Y99), R655 (7Y00 / 7Z01)

Requisitos del sistema	
Sistemas operativos compatibles	Microsoft Windows Server version 1709, Microsoft Windows Server version 1803, Red Hat Enterprise Linux 6.10, Red Hat Enterprise Linux 6.9, Red Hat Enterprise Linux 7.3, Red Hat Enterprise Linux 7.4, Red Hat Enterprise Linux 7.5, Red Hat Enterprise Linux 7.6, Red Hat Enterprise Linux 7.7, Red Hat Enterprise Linux 8.0, SUSE Linux Enterprise Server 12 SP2, SUSE Linux Enterprise Server 12 SP2 with Xen, SUSE Linux Enterprise Server 12 SP3, SUSE Linux Enterprise Server 12 SP3 with Xen, SUSE Linux Enterprise Server 12 SP4, SUSE Linux Enterprise Server 12 SP4 with Xen, SUSE Linux Enterprise Server 15, SUSE Linux Enterprise Server 15 SP1, SUSE Linux Enterprise Server 15 SP1 with Xen, SUSE Linux Enterprise Server 15 with Xen, VMware vSphere Hypervisor (ESXi) 6.0 U3, VMware vSphere Hypervisor (ESXi) 6.5, VMware vSphere Hypervisor (ESXi) 6.5 U1, VMware vSphere Hypervisor (ESXi) 6.5 U2, VMware vSphere Hypervisor (ESXi) 6.5 U3, VMware vSphere Hypervisor (ESXi) 6.7, VMware vSphere Hypervisor (ESXi) 6.7 U1, VMware vSphere Hypervisor (ESXi) 6.7 U2, VMware vSphere Hypervisor (ESXi) 6.7 U3
Sistema operativo de servidor soportado	SUSE Linux Enterprise Server 12, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Condiciones ambientales	
Intervalo de temperatura operativa	10 - 35 °C
Intervalo de humedad relativa para funcionamiento	20 - 80%

Peso y dimensiones	
Ancho	69 mm
Profundidad	132 mm
Altura	19 mm

Detalles técnicos	
Certificados de conformidad	RoHS

Datos logísticos	
Código de Sistema de Armomización (SA)	85176990
Otras características	
Temperatura mínima de operación	10 °C
Máxima temperatura	35 °C
Soporte de control de flujo	✔



0889488497287



889488497287

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-JUL-2025. Prints or copies of Information are only valid on the printed Publication date