



TP-Link Archer NX500 router inalámbrico Gigabit Ethernet Doble banda (2,4 GHz / 5 GHz) 5G Blanco

Marca : TP-Link

Familia de productos: Archer Código del producto: ARCHER NX500

Nombre del producto : NX500

TP-Link Archer NX500. Tipo de conexión WAN: RJ-45. Banda Wi-Fi: Doble banda (2,4 GHz / 5 GHz), Estándar Wi-Fi: Wi-Fi 6 (802.11ax), Tasa de transferencia de datos WLAN (máx.): 2402 Mbit/s. Tipo de interfaz Ethernet LAN: Gigabit Ethernet, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s, Tecnología de cableado: 10/100/1000Base-T(X). Generación de red móvil: 5G, Estándares 3G: DC-HSDPA, HSPA, HSPA+, UMTS, Estándar 4G: LTE-TDD & LTE-FDD. Algoritmos de seguridad soportados: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK



Conexión WAN		Seguridad	
Ethernet WAN *	✓	Filtro de dirección IP	✓
DSL WAN *	✗	Filtro de URL	✓
Ranura para tarjeta SIM *	✓	Soporte DMZ	✓
Tipo de conexión WAN	RJ-45	Protocolos	
Características de LAN inalámbrico		DHCP, cliente	✓
Banda Wi-Fi *	Doble banda (2,4 GHz / 5 GHz)	DHCP, servidor	✓
Estándar Wi-Fi *	Wi-Fi 6 (802.11ax)	Conectar y usar universal (UPnP, Universal Plug and Play)	✓
Tasa de transferencia de datos WLAN (máx.) *	2402 Mbit/s	Protocolos de red compatibles	IPv4, IPv6
Wi-Fi estándares	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Diseño	
Conexión		Color del producto	Blanco
Ethernet *	✓	Pantalla incorporada	✗
Tipo de interfaz Ethernet LAN *	Gigabit Ethernet	Tipo de producto *	Enrutador de escritorio/poste
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s	Aprobaciones regulatoras	
Tecnología de cableado	10/100/1000Base-T(X)	Certificados de conformidad	CE, RoHS
Reenvío de puertos	✓	Contenido del embalaje	
Port triggering (Desencadenamiento o lanzamiento de puertos)	✓	Cables incluidos	LAN (RJ-45)
DNS dinámico	✓	Adaptador AC incluido	✓
Número de redes de invitados (2,4 GHz)	1	Guía de instalación rápida	✓
		Antena	
		Diseño de la antena *	Interno y externo

Conexión		Antena	
Número de redes de invitados (5GHz)	1	Tipo de conector de antena	SMA
Potencia máxima de transmisión (2,4 GHz)	20 dBmW	Cantidad de antenas	10
Potencia máxima de transmisión (5 GHz)	30 dBmW	Control de energía	
Redes móviles		Alimentación *	Corriente alterna
Generación de red móvil	5G	Voltaje de entrada AC	100 - 240 V
Estándares 3G	DC-HSDPA, HSPA, HSPA+, UMTS	Frecuencia de entrada AC	50/60 Hz
Estándar 4G	LTE-TDD & LTE-FDD	Voltaje de salida	12 V
Bandas 5G compatibles	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Corriente de salida	2 A
Admite bandas 4G	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Condiciones ambientales	
Bandas 3G soportadas	850,900,2100 MHz	Intervalo de temperatura operativa	0 - 40 °C
Tipo de tarjeta SIM	NanoSIM	Intervalo de temperatura de almacenaje	-40 - 70 °C
Puertos e Interfaces		Intervalo de humedad relativa para funcionamiento	10 - 90%
Ethernet LAN (RJ-45) cantidad de puertos *	2	Intervalo de humedad relativa durante almacenaje	5 - 90%
Puerto USB *	✗	Requisitos del sistema	
Características de administración		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows RT 8.1, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
Wi-Fi Multimedia (WMM)/(WME)	✓	Sistema operativo Windows soportado	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows RT 8.1, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Calidad de servicio (QoS) soporte	✓	Sistema operativo Linux soportado	✓
Botón de restaurar	✓	Sistema operativo MAC soportado	✓
Seguridad por pulsador WPS	✓	Compatible con Mac	✓
Seguridad		Peso y dimensiones	
Algoritmos de seguridad soportados	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Ancho	99 mm
El acceso de invitados	✓	Profundidad	99 mm
Prevención de ataques DoS	✓	Altura	190 mm
Control parental	✓	Empaquetado	
Filtrado	✓	Tipo de embalaje	Caja
		Número de productos incluidos	1 pieza(s)



1210002601634



1210002601610

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.