APC E3SUPS15K3IB1 sistema de alimentación ininterrumpida (UPS) Doble conversión (en línea) 15 kVA 15000 W





Marca : APC

Código del producto: E3SUPS15K3IB1

Nombre del producto : E3SUPS15K3IB1

APC E3SUPS15K3IB1. Topología UPS: Doble conversión (en línea), Capacidad de potencia de salida (VA): 15 kVA, Potencia de salida: 15000 W. Tecnología de batería: Sealed Lead Acid (VRLA), Capacidad de la batería: 40 Ah, Voltaje de la pila: 240 V. Color del producto: Blanco, Código IP (International Protection): IP20. Certificados de conformidad: RoHS, Certificación: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE. Ancho: 380 mm, Profundidad: 907 mm, Altura: 1400 mm

Características	
Topología UPS *	Doble conversión (en línea)
Capacidad de potencia de salida (VA) *	15 kVA
Potencia de salida *	15000 W
Voltaje de entrada de operación (min) *	380 V
Voltaje de entrada de operación (max) *	415 V
Frecuencia de entrada *	45/65 Hz
Voltaje de operación de salida (min)	220 V
Voltaje de operación de salida (max)	240 V
Frecuencia de salida	50/60 Hz
Factor de poder	0,99
Factor de cima	3:1
Nivel de ruido	60 dB

Batería	
Tecnología de batería	Sealed Lead Acid (VRLA)
Capacidad de la batería	40 Ah
Voltaje de la pila	240 V
Numero de baterías soportadas	1

Diseño	
Color del producto *	Blanco

Diseño	
Código IP (International Protection)	IP20

Condiciones ambientales	
Intervalo de temperatura operativa	0 - 40 °C
Intervalo de temperatura de almacenaje	-15 - 40 °C
Intervalo de humedad relativa para funcionamiento	0 - 95%
Intervalo de humedad relativa durante almacenaje	0 - 95%

Aprobaciones reguladoras	
Certificados de conformidad	RoHS
Certificación	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE

Peso y dimensiones	
Ancho	380 mm
Profundidad	907 mm
Altura	1400 mm
Peso	71,2 kg

Empaquetado	
Ancho del paquete	563 mm
Profundidad del paquete	1014 mm
Altura del paquete	1640 mm
Peso del paquete	173 kg

Datos logísticos	
Código de Sistema de Armomización (SA)	85078000



0731304428176



731304428176

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-JUL-2025. Prints or copies of Information are only valid on the printed Publication date