



## TP-Link Omada IES208G switch Gestionado Gigabit Ethernet (10/100/1000)

**Marca :** TP-Link

**Familia de productos:** Omada **Código del producto:** IES208G

**Nombre del producto :**  
IES208G



TP-Link Omada IES208G. Tipo de interruptor: Gestionado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 6. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 16 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Voltaje de entrada DC: 9.6 - 60 V. Montaje de pared

| Características de administración                           |                                                                                           | Conexión                                        |               |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------|---------------|
| Tipo de interruptor *                                       | Gestionado                                                                                | Auto-negociación                                | ✓             |
| Calidad de servicio (QoS) soporte                           | ✓                                                                                         | Transmisión de datos                            |               |
| Administración basada en web                                | ✓                                                                                         | Capacidad de conmutación *                      | 16 Gbit/s     |
| Administrado a través de la nube                            | ✓                                                                                         | Tasa de reenvío                                 | 11,9 Mpps     |
| Puertos e Interfaces                                        |                                                                                           | Tabla de direcciones MAC *                      | 8000 entradas |
| Cantidad de puertos básicos de conmutación RJ-45 Ethernet * | 6                                                                                         | Jumbo Frames, soporte                           | ✓             |
| Puertos tipo básico de conmutación RJ-45 Ethernet *         | Gigabit Ethernet (10/100/1000)                                                            | Tramas Jumbo                                    | 15000         |
| Combo SFP Cantidad de puertos                               | 2                                                                                         | Seguridad                                       |               |
| Conexión                                                    |                                                                                           | IGMP                                            | ✓             |
| Estándares de red *                                         | IEEE 802.1D, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | Seguridad de puerto estático                    | ✓             |
| Soporte 10G *                                               | ✗                                                                                         | Diseño                                          |               |
| Espejeo de puertos                                          | ✓                                                                                         | Montaje de pared                                | ✓             |
| Soporte de control de flujo                                 | ✓                                                                                         | Montaje en carril DIN                           | ✓             |
| Adición de vínculos                                         | ✓                                                                                         | Control de energía                              |               |
| Control de transmisión de tormentas                         | ✓                                                                                         | Fuente de energía *                             | CC            |
| Auto MDI / MDI-X                                            | ✓                                                                                         | Suministro de energía redundante (RPS), soporte | ✓             |
| Protocolo de árbol de expansión                             | ✓                                                                                         | Voltaje de entrada DC                           | 9.6 - 60 V    |
|                                                             |                                                                                           | Alimentación a través de Ethernet (PoE)         |               |
|                                                             |                                                                                           | Energía sobre Ethernet (PoE) *                  | ✗             |
|                                                             |                                                                                           | Peso y dimensiones                              |               |
|                                                             |                                                                                           | Ancho                                           | 129 mm        |
|                                                             |                                                                                           | Profundidad                                     | 95 mm         |
|                                                             |                                                                                           | Altura                                          | 45 mm         |



1210002602099

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.