

StarTech.com Switch Conmutador KVM de Cable con 2 Puertos VGA USB Alimentado por USB con Interruptor Remoto

Marca : StarTech.com

Código del producto: SV211USB

Nombre del producto : Switch Conmutador KVM de Cable con 2 Puertos VGA USB Alimentado por USB con Interruptor Remoto



StarTech.com Switch Conmutador KVM de Cable con 2 Puertos VGA USB Alimentado por USB con Interruptor Remoto

StarTech.com Switch Conmutador KVM de Cable con 2 Puertos VGA USB Alimentado por USB con Interruptor Remoto. Tipo de puerto de teclado: USB, Tipo de puerto de ratón: USB, Tipo de puerto de vídeo: VGA. Máxima resolución: 2048 x 1536 Píxeles, Resolución (máxima digital): 2048 x 1536 Píxeles. Color del producto: Negro, Material de la carcasa: Plástico, Longitud de cable: 0,85 m. Sistema operativo Windows soportado: Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64,...., Sistema operativo MAC soportado: Mac OS 9.0, Mac OS 9.1, Mac OS 9.2, Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.2..., Sistema operativo de servidor soportado: Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows.... Certificados de conformidad: RoHS



Puertos e Interfaces		Requisitos del sistema	
Número de computadoras controladas *	2	Sistema operativo MAC soportado	Mac OS 9.0, Mac OS 9.1, Mac OS 9.2, Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Tipo de puerto de teclado *	USB		
Tipo de puerto de ratón *	USB		
Tipo de puerto de vídeo *	VGA		
Puertos de la consola *	USB A, VGA (D-Sub)		
Cantidad de puertos USB de la consola	2	Sistema operativo de servidor soportado	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019
Conexión de audio	✗		
Desempeño		Sostenibilidad	
Máxima resolución *	2048 x 1536 Píxeles	Certificados de conformidad	RoHS
Resolución (máxima digital)	2048 x 1536 Píxeles	Condiciones ambientales	
Compatibilidad con Hot-Plug	✓	Intervalo de temperatura operativa	0 - 40 °C
Conexión en cadena	✗	Intervalo de temperatura de almacenaje	-20 - 60 °C
Diseño		Intervalo de humedad relativa para funcionamiento	0 - 90%
Montaje en rack *	✗	Peso y dimensiones	
Color del producto *	Negro	Ancho	66 mm
Material de la carcasa	Plástico	Profundidad	88 mm
Longitud de cable	0,85 m	Altura	23 mm
Indicadores LED	✓	Peso	380 g
Certificación	CE, FCC	Empaquetado	
Exhibición		Ancho del paquete	164 mm
Pantalla incorporada *	✗	Profundidad del paquete	250 mm
Control de energía		Altura del paquete	63 mm
USB con suministro de corriente	✓		

Requisitos del sistema		Empaquetado	
Sistema operativo Windows soportado	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	Peso del paquete	435 g
		Contenido del embalaje	
		Manual de usuario	✓
		Otras características	
		Soporte de audio	✓
		Control IP	✗
		Datos logísticos	
		Código de Sistema de Armomización (SA)	85176200



0065030858625



065030858625



5054242255051

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.