




Lenovo 11S30008SP sistema de video conferencia Ethernet All-in-One thin client

Marca : Lenovo

Código del producto: 11S30008SP

Nombre del producto : 11S30008SP



- Intel Core i5-1145G7E (4C/8T, 1.5/4.1GHz, 8MB)
- 8GB DDR4-3200
- 256GB SSD M.2 2280 PCIe 3.0x4 NVMe
- Intel Iris Xe Graphics
- Windows 10 IoT Enterprise CLB 64

Intel Core i5-1145G7E (4C/8T, 1.5/4.1GHz, 8MB), 8GB DDR4-3200, 256GB SSD M.2 2280 PCIe 3.0x4 NVMe, 10.1" Display on ThinkSmart Touch Controller, Intel Iris Xe Graphics, Intel AX201 11ax 2x2 + BT5.0 vPro, ThinkSmart Cam, Windows 10 IoT Enterprise CLB 64

Lenovo 11S30008SP sistema de video conferencia Ethernet All-in-One thin client:

Colaboración más Smart con Teams con la tecnología A/V existente

Opta por una colaboración más Smart en salas de reuniones de todos los tamaños con nuestro kit ThinkSmart Core + Controller Kit para Microsoft Teams Rooms, ideal para espacios que ya tienen tecnología A/V. El kit incluye ThinkSmart Core, que es un dispositivo informático con la plataforma Intel vPro® y está certificado para Microsoft Teams, la pantalla Controller, Premier Support y nuestro software ThinkSmart Manager Premium para la implantación y la administración en remoto, entre otras funciones.



Desempeño		Conexión	
Bluetooth	✓	Ethernet *	✓
Versión de Bluetooth	5.0	Ethernet LAN, velocidad de transferencia de datos	100,1000 Mbit/s
Color del producto *	Negro, Rojo	Wifi	✓
Tipo de producto *	All-in-One thin client	Wi-Fi estándares	Wi-Fi 6 (802.11ax)
Audio		Exhibición	
Altavoces incorporados	✓	Diagonal de la pantalla	25,6 cm (10.1")
Número de altavoces	4	Resolución de la pantalla	1280 x 800 Pixeles
Potencia estimada RMS	20 W	Pantalla táctil	✓
Memoria		Brillo de pantalla	340 cd / m²
Tipo de memoria interna	DDR4-SDRAM	Pantalla antirreflectante	✓
Capacidad total de almacenaje	256 GB	Características	
Puertos e Interfaces		Ranura para cable de seguridad	✓
Número de puertos HDMI	2	Tipo de ranura de bloqueo del cable	Kensington
Cantidad de puertos tipo A USB 3.2 Gen 1 (3.1 Gen 1)	1	Sistema informático	
Cantidad de puertos tipo A USB 3.2 Gen 2 (3.1 Gen 2)	2	Familia de procesador	Intel® Core™ i5
Cantidad de puertos tipo C USB 3.2 Gen 1 (3.1 Gen 1)	1	Generación del procesador	Intel® Core™ i5 de 11ma Generación
Ethernet LAN (RJ-45) cantidad de puertos	1	Modelo del procesador	1145G7E
		montaje VESA	✓
		Sistema operativo instalado	Windows 10 IoT Enterprise

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.