

StarTech.com Cable Adaptador USB a Serie de 3m - Retención COM - FTDI - USB a DB9 RS232 Serial - Tornillos Intercambiables - Protección ESD - Windows/macOS/Linux

Marca : StarTech.com

Código del producto: 1P10FFC-USB-SERIAL

Nombre del producto : Cable Adaptador USB a Serie de 3m - Retención COM - FTDI - USB a DB9 RS232 Serial - Tornillos Intercambiables - Protección ESD - Windows/macOS/Linux



StarTech.com Cable Adaptador USB a Serie de 3m - Retención COM - FTDI - USB a DB9 RS232 Serial - Tornillos Intercambiables  
StarTech.com Cable Adaptador USB a Serie de 3m - Retención COM - FTDI - USB a DB9 RS232 Serial - Tornillos Intercambiables - Protección ESD - Windows/macOS/Linux. Color del producto: Negro, Longitud de cable: 3 m, Conector 1: USB tipo A. Ancho del paquete: 220 mm, Profundidad del paquete: 1 mm, Altura del paquete: 200 mm. Ancho: 34 mm, Altura: 16 mm, Peso: 120 g. Ancho de la caja principal: 570 mm, Longitud de la caja: 355 mm, Alto de la caja principal: 290 mm



| Características                            |                                                       | Características                                   |                                                                                                                                    |
|--------------------------------------------|-------------------------------------------------------|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Color del producto *                       | Negro                                                 | Sistema operativo de servidor soportado           | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022 |
| Longitud de cable *                        | 3 m                                                   |                                                   |                                                                                                                                    |
| Conector 1 *                               | USB tipo A                                            | Empaquetado                                       |                                                                                                                                    |
| Conector 2 *                               | DB-9                                                  | Ancho del paquete                                 | 220 mm                                                                                                                             |
| Género del conector 1                      | Macho                                                 | Profundidad del paquete                           | 1 mm                                                                                                                               |
| Género del conector 2                      | Macho                                                 | Altura del paquete                                | 200 mm                                                                                                                             |
| Factor de forma de conector 1              | Derecho                                               | Peso del paquete                                  | 130 g                                                                                                                              |
| Factor de forma de conector 2              | Derecho                                               | Condiciones ambientales                           |                                                                                                                                    |
| Circuito integrado                         | FTDI - FT232R                                         | Intervalo de temperatura operativa                | -40 - 80 °C                                                                                                                        |
| Velocidad de transmisión                   | 921,6 Kbit/s                                          | Intervalo de temperatura de almacenaje            | -40 - 80 °C                                                                                                                        |
| Bits de datos                              | 7, 8                                                  | Intervalo de humedad relativa para funcionamiento | 0 - 95%                                                                                                                            |
| PEPS (Primeras Entradas, Primeras Salidas) | 256 B                                                 | Peso y dimensiones                                |                                                                                                                                    |
| Bit de paridad                             | Even, Mark, No, Unidad de disco óptico (ODD), Espacio | Ancho                                             | 34 mm                                                                                                                              |
| Bits de parada                             | 1, 2                                                  | Altura                                            | 16 mm                                                                                                                              |
|                                            |                                                       | Peso                                              | 120 g                                                                                                                              |
|                                            |                                                       | Datos logísticos                                  |                                                                                                                                    |
|                                            |                                                       | Ancho de la caja principal                        | 570 mm                                                                                                                             |
|                                            |                                                       | Longitud de la caja                               | 355 mm                                                                                                                             |
|                                            |                                                       | Alto de la caja principal                         | 290 mm                                                                                                                             |
|                                            |                                                       | Cantidad por caja                                 | 100 pieza(s)                                                                                                                       |

| Características                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sistema operativo Windows soportado | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 Enterprise, Windows 11 Enterprise x64, Windows 11 Home, Windows 11 Pro, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64 |
| Sistema operativo MAC soportado     | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Sistema operativo Linux soportado   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |



0065030898331



065030898331

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.