



Lenovo 4XB7A82264 unidad de estado sólido 240 GB Serial ATA III 3D TLC NAND

Marca : Lenovo

Código del producto: 4XB7A82264

Nombre del producto : 4XB7A82264

Lenovo 4XB7A82264. SDD, capacidad: 240 GB, Velocidad de transferencia de datos: 6 Gbit/s, Componente para: Servidor/estación de trabajo



Características		Características	
SDD, capacidad *	240 GB	Certificación	Micron Green Standard Built with sulfur resistant resistors CE (Europe): EN 55032 Class B, RoHS UKCA (UK): SI 2016/1091 Class B and SI 2012/3032 RoHS FCC: CFR Title 47, Part 15 Class B UL/cUL: approval to UL-60950-1, 2nd Edition, IEC 60950-1:2005 (2nd Edition); EN 60950-1 (2006) + A11:2009+ A1:2010 + A12:2011 + A2:2013 BSMI (Taiwan): approval to CNS 13438 Class B and CNS 15663 RCM (Australia, New Zealand): AS/NZS CISPR32 Class B KC RRA (Korea): approval to KN32 Class B, KN 35 Class B W.E.E.E.: compliance with EU WEEE directive 2012/19/EC TUV (Germany): approval to IEC60950/EN60950 VCCI (Japan): 2015-04 Class B IC (Canada): ICES-003 Class B Morocco: approval to EN55032/EN55024 Class B UkrSEPRO (Ukraine): EN55032 Class B, IEC60950/EN60950, RoHS (Resolution 2017 No. 139)
Interfaz *	Serial ATA III		
Tipo de memoria *	3D TLC NAND		
Componente para *	Servidor/estación de trabajo		
Velocidad de transferencia de datos	6 Gbit/s		
Lectura aleatoria (4KB)	75000 IOPS		
Escritura aleatoria (4KB)	37000 IOPS		
Latencia de lectura	170 μs		
Latencia de escritura	150 μs		
Soporte S.M.A.R.T.	✓		
Hot-swap	✓		
Uncorrectable Bit Error Rate (UBER)	< 1 per 10^17 bits read		
Tiempo medio entre fallos	3000000 h		
Escrituras en el disco por día (DWPd, Drive writes per day)	1,5		
Control de energía			
Consumo de energía (lectura)		2,5 W	
Consumo de energía (escritura)		3 W	
Peso y dimensiones			
Ancho		70 mm	
Profundidad		100 mm	
Altura		7 mm	
Peso		70 g	
Condiciones ambientales			
Intervalo de temperatura operativa		0 - 70 °C	
Intervalo de temperatura de almacenaje		-40 - 85 °C	
Intervalo de humedad relativa para funcionamiento		5 - 95%	
Vibración no operativa		3,13 G	
Golpe (fuera de operación)		1500 G	
Otras características			
Productos compatibles		ThinkSystem	



0889488633364



889488633364

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.