

CyberPower PDU24005 unidad de distribución de energía (PDU) 10 salidas AC 1U Negro

Marca : CyberPower

Código del producto: PDU24005

Nombre del producto : PDU24005

CyberPower PDU24005. PDU tipos: Regulado, Capacidad del rack: 1U, Tipo: Monofásico. Cantidad de salidas AC: 10 salidas AC, Tipo de salida AC: C13 acoplador, C19 acoplador, Conector: C20 acoplador. Indicadores LED: Enlace, Estado, Longitud de cable: 3,05 m. Voltaje nominal de entrada: 200 - 240 V, Máxima corriente: 12 A, Frecuencia de entrada AC: 50 / 60 Hz. Certificados de conformidad: CB, CE, Comisión Federal de Comunicaciones (FCC) de Estados Unidos, RoHS, UL, Certificación: FCC Class A, UL62368, EN 55032 Class A, IEC 62368



Design		Certificates	
PDU types *	Metered	Certification	FCC Class A, UL62368, EN 55032 Class A, IEC 62368
Type	Single-phase	Sustainability	
Rack capacity *	1U	Sustainability compliance	✓
Mounting	Horizontal	Operational conditions	
Housing material	Steel	Operating temperature (T-T)	0 - 45 °C
Product colour	Black	Storage temperature (T-T)	-15 - 95 °C
Display	LCD	Operating relative humidity (H-H)	0 - 95%
Ports & interfaces		Storage relative humidity (H-H)	0 - 95%
AC outlets quantity *	10 AC outlet(s)	Operating altitude	0 - 4000 m
Power plug	C20 coupler	Non-operating altitude	0 - 15000 m
AC outlet types *	C13 coupler, C19 coupler	Operating temperature (T-T)	32 - 113 °F
Serial ports quantity	1	Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Width	433 mm
USB ports quantity	1	Depth	215 mm
Features		Height	44 mm
LED indicators	Link, Status	Weight	3.2 kg
Cable length	3.05 m	Packaging content	
Management features		Packaging content	PDU24005, User's Manual, Cord Retention Tray, Mounting Brackets, Cable Ties, Screw Kit, Power Cord, Serial Cable
Firmware upgradeable	✓	Packaging data	
Power		Package weight	6 kg
Nominal input voltage *	200 - 240 V	Package width	550 mm
AC input frequency	50 / 60 Hz	Package depth	398 mm
Maximum current *	12 A	Package height	125 mm
Nominal output voltage	200 - 240 V		
Power protection features	Overload		
Circuit breaker	✓		

Certificates		Logistics data	
Compliance certificates	CB, CE, Federal Communications Commission (FCC), RoHS, UL	Warranty period	2 year(s)



4711027799797



0649532933358



649532933358

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAY-2025. Prints or copies of Information are only valid on the printed Publication date