

CyberPower PR1000ERT2U sistema de alimentación ininterrumpida (UPS) Línea interactiva 1 kVA 1000 W 10 salidas AC

Marca : CyberPower

Código del producto: PR1000ERT2U



Nombre del producto : PR1000ERT2U

CyberPower PR1000ERT2U. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1 kVA, Potencia de salida: 1000 W. Tipo de salida AC: C13 acoplador, Conector: C14 acoplador, Cantidad de salidas AC: 10 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo típico de respaldo a carga completa: 7 min, Tiempo típico de respaldo a media carga: 21 min. Factor de forma: Montaje en rack/Torre o Montaje en bastidor/Torre, Color del producto: Negro, Material de la carcasa: Metal. Certificados de conformidad: CE, Comisión Federal de Comunicaciones (FCC) de Estados Unidos, RCM, RoHS, UKCA, UL, VCCI



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at full load	7 min
Output power capacity *	1 kVA	Typical backup time at half load	21 min
Output power *	1000 W	Battery recharge time	3 h
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	159 V	Design	
Input operation voltage (max) *	288 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	10 A		
Surge energy rating	2430 J	Form factor *	Rackmount/Tower
Response time	4 ms	Housing material	Metal
Heat dissipation	47.4 BTU/h	Rack capacity	2U
Number of input phases	1	Cable length	1.8 m
Number of output phases	1	Cooling type	Active
Output power factor	1	Built-in fan	✓
Power Factor Correction (PFC) type	Active	Product colour *	Black
Emergency Power Off (EPO)	✓	Control type	Buttons
EMI/RFI noise filtering	✓	Display type	LCD
Noise level	52.5 dB	LED indicators	Fault, Power, Status
Surge protection	✓	Operational conditions	
Surge protection features	Network		
Power protection features	Overload		
Audible alarm(s)	✓		
Web-based management	✓	Operating temperature (T-T)	0 - 40 °C
Management protocols	SNMP/HTTP	Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UKCA, UL, VCCI

Features		Packaging content	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Rack mount kit	✓
Ports & interfaces		Cables included	Serial, USB cable
		Manual	✓
		Sustainability	
		Sustainability compliance	✓
		Sustainability certificates	ENERGY STAR
		Weight & dimensions	
		Width	433 mm
		Depth	412 mm
		Height	86.5 mm
		Weight	22.4 kg
Battery		Packaging data	
		Package width	560 mm
		Package depth	530 mm
		Package height	275 mm
		Package weight	29 kg
		Logistics data	
		Harmonized System (HS) code	8504408590
		Warranty period	3 year(s)
		Country of origin	China
		Other features	
		Battery type	RBP0128



4712856277623

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2025. Prints or copies of Information are only valid on the printed Publication date