

CyberPower PR3000ERT2U sistema de alimentación ininterrumpida (UPS) Línea interactiva 3 kVA 3000 W 8 salidas AC

Marca : CyberPower

Código del producto: PR3000ERT2U

Nombre del producto : PR3000ERT2U



CyberPower PR3000ERT2U. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 3 kVA, Potencia de salida: 3000 W. Tipo de salida AC: C13 acoplador, C19 acoplador, Conector: C20 acoplador, Cantidad de salidas AC: 8 salidas AC. Tecnología de batería: Sealed Lead Acid (VRLA), Tiempo típico de respaldo a carga completa: 1,3 min, Tiempo típico de respaldo a media carga: 6,4 min. Factor de forma: Montaje en rack/Torre o Montaje en bastidor/Torre, Color del producto: Negro, Material de la carcasa: Metal. Certificados de conformidad: RoHS



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at full load	1.3 min
Output power capacity *	3 kVA	Typical backup time at half load	6.4 min
Output power *	3000 W	Battery recharge time	3 h
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	159 V	Design	
Input operation voltage (max) *	288 V	Form factor *	Rackmount/Tower
Input frequency *	50/60 Hz	Housing material	Metal
Output operation voltage (min)	220 V	Rack capacity	2U
Output operation voltage (max)	240 V	Cable length	2.4 m
Output frequency	50/60 Hz	Cooling type	Active
Automatic Voltage Regulation (AVR)	✓	Built-in fan	✓
Maximum current	10 A	Product colour *	Black
Surge energy rating	2430 J	Control type	Buttons
Response time	4 ms	Display type	LCD
Heat dissipation	120.8 BTU/h	LED indicators	Fault, Power, Status
Number of input phases	1	Operational conditions	
Number of output phases	1	Operating temperature (T-T)	0 - 40 °C
Power factor	1	Storage temperature (T-T)	-15 - 45 °C
Power Factor Correction (PFC) type	Active	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Operating altitude	0 - 3000 m
Noise level	57.5 dB	Non-operating altitude	0 - 15000 m
Surge protection	✓	Certificates	
Surge protection features	Network	Compliance certificates	RoHS
Power protection features	Overload	Packaging content	
Audible alarm(s)	✓	Rack mount kit	✓
Management protocols	SNMP/HTTP	Cables included	Serial, USB cable
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm		

Ports & interfaces		Packaging content	
AC outlet types	C13 coupler, C19 coupler	Manual	✓
Power plug	C20 coupler	Sustainability	
AC outlets quantity	8 AC outlet(s)	Sustainability compliance	✓
USB port	✓	Sustainability certificates	ENERGY STAR
Serial interface	✓	Weight & dimensions	
Serial interface type	RS-232	Width	433 mm
Serial ports quantity	1	Depth	500 mm
RS-232 ports	1	Height	86.5 mm
Ethernet LAN (RJ-45) ports	2	Weight	32.3 kg
Emergency Power Off (EPO) connector	✓	Packaging data	
Battery		Package width	560 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	620 mm
Number of batteries supported	1	Package height	275 mm
		Package weight	40.3 kg
		Logistics data	
		Harmonized System (HS) code	8504408590
		Warranty period	3 year(s)
		Country of origin	China
		Other features	
		Battery type	RBP0129



4712856277562

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAY-2025. Prints or copies of Information are only valid on the printed Publication date